

VZ-2.UHD Document Camera



Outstanding imaging technology for education

VZ-2.UHD Document Camera / Visualizer

The VZ-2.UHD Visualizer system demonstrates that simplicity truly is the ultimate sophistication. Drawing on more than 50 years' experience and expertise, we have engineered a superb new entry level document camera system, ideal for inspiring creative teaching and learning, both inside and outside of the classroom.

This elegant, compact, affordable system, features outstanding picture quality, plus the same robust design, and unrivalled ease of use, that is found throughout the entire WolfVision product line. It is a first-class 'live' imaging tool, equally suitable for supporting in-classroom, online or hybrid learning environments.

Driving Knowledge Creation



Our Vision

When you've got something to say, we believe it is important that getting your message across and making an impact should be as easy as possible.

Our aim is to help you to explain it better, to give you the freedom to share your knowledge and collaborate with others - however you want, and whenever you want, when your audience is in the same room or on the other side of the world.

Because knowledge matters to all of us.

Advanced yet simple

4K Stunning picture quality!

Bring your classes to life using our ultra-high resolution 4K UHD camera with 30 frames per second (60 fps in all other resolutions), ensuring smoothness of motion, and an outstanding image resolution of 1300 lines.



Versatile zoom range

With 24x Zoom even the finest details are easily shown onscreen. This Visualizer handles both A4 portrait and A3-sized materials, and delivers the incredible, crisp, true-to-life on-screen images that students remember long after the session is over.



Shake-free imaging!

Simply touch the unit to appreciate its solid construction. Unlike other compact doc cams, it doesn't wobble when you operate it. Onscreen images are always shakefree, ensuring there are no onscreen distractions for students.



Imaging around the room!

Using the normal working area, filming yourself, or even picking up an object from behind the Visualizer are all possible using the 192° rotating camera.



Energy efficient

The VZ-2.UHD is extremely energy efficient, using only 18 watts in operating mode. It can also be configured to switch off automatically at a pre-defined time if required.



No need to adjust the light!

Powerful fixed LED lights provide smooth, natural illumination, optimised for every part of the pickup area. Hotspots are eliminated, and on-screen images are tack sharp and distortion-free, even at the edges of the displayed image.



Remote management tools

The VZ-2.UHD unit has a network interface which enables it to be used with our vSolution Link Pro software, providing easy remote setup, monitoring, management and updating of large numbers of devices.

Visualizers built to last

High quality components for outstanding mechanical quality, durability, and reliability, plus a 5 year warranty. These Visualizer systems are built to last!





Capture, Share, Inspire



Flexible solution for hybrid learning

Use the 4K UHD rotating camera as a webcam for a flexible web conferencing experience. Switch camera positions easily between your content materials and yourself as and when needed.

Even better when combined!

Use our dedicated app to send your Visualizer images to your interactive whiteboard. Add them easily into classroom sessions, and even control your Visualizer using your interactive whiteboard.





Outstanding connectivity options

With HDMI In and HDMI out ports plus a LAN network interface, it's easy to integrate the VZ-2.UHD into your setup. The USB 2.0 host port is useful for saving images onto a USB stick and the USB 3.0 device port can be used for connecting to a computer.

Designed for ease of use

Continuous autofocus ensures on-screen images always look superb, and the convenient built-in touchscreen user interface ensures quick and easy operation of all controls.



Technical specifications

Cernel / Errors per second CMCS 1/24** 4C.145.20 terms per second 8D (pin is) of the resolution) Ebichs peck of carnen server SB44 / 2102 (pipors, 8.47 response) Name segring cardyot (Cardyot resolution) 21050 (PiA4 (SB50 / 2105), 720, HD (1280 / 720,	Features	VZ-2.UHD
Election packed oranne service 3884 > 2182 (paper, 8.47 megacikeli) Native signar orange orange discussion organization orange orange discussion and the service orange discussion orange discussion and the service orange discussion orange discussion and the service orange discussion orange discussion and the service orange discussion orange discussion orange discussion and the service orange discussion orange discussion orange discussion discussion discussion discussion discussion and discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discussion discusion disc		CMOS 1/2.8" 4K UHD 30 frames per second (60 fps in all other resolutions)
Convented vedeescen cutput signals (16.8 and 16.10) 1080p FHD (120 x 1080), 720p HD (120 x 723) Image resolution 1300 lines Explicitness control Automatic and manual White balances adjustment Automatic and manual Adjustable colour settings Veis Facial modes High measure adjustment Adjustable colour settings Veis Facial modes High measure adjustment Adjustable colour settings Veis Facial modes High measure adjustment On-screen meau Veis, tocal/screen with wayee-through meanu & facesword-protected ad networded functions Veis color face functions Veis, tocal/screen with wayee -through meanu & facesword-protected ad networded functions Veis color face functions Veis, tocal/screen with wayee -through meanu & facesword-protected ad networded functions Veis color face functions ad protections Veis, tocal/screen with wayee -through meanu & facesword-protected ad networded functions Veis color face functions ad protection and wording surface Veis, tocal/screen with wayee -through meanu & facesword-protected ad networded Mass do face function ad wording surface Length: 50 mm, Woth: 427 mm. Mass do face function ad wording surface Length: 50 mm, Woth:		3864 × 2192 (approx. 8.47 megapixels)
Image resolutionISB0 InseBergintenso controlAutomatic and manualMinist testing controlAutomatic and manualMinist testing controlVesFocus modesHigh speed continuous audioccus, manual focusFocus modesHigh speed continuous audioccus, manual focusOn scene manuVes, touthscene with subjec through time & assessord protected advanced functionsVestation Link Pho software for memore management & firmware updatesVes, touthscene with subjec through time & assessord protected advanced functionsVestation Link Pho software for memore management & firmware updatesVes, touthscene with subjec through time & assessord protected advanced functionsVestation Link Pho software for memore management & firmware updatesVes, val USE, Lev, and VSE, Lev, and VS	Native signal output / Output resolution	2160p UHD 444 (3840 x 2160)
Participants Automatic and manual White balance adjustment Automatic and manual Adjustation coduri settings Net Adjustation coduri settings Net On-sinteen manu Net, touchacineen with insper-through minu & password-protected ischanood functions On-sinteen manu Net, touchacineen with insper-through minu & password-protected ischanood functions Visibilitor Link Pro activerse for menote management & firmwere updates Net, included (Windows 10, Windows Server 2012 R2 & 2018, Windows Web Server, mac/CS) First firmere updates Yes, included (Windows 10, Windows Server 2012 R2 & 2018, Windows Web Server, mac/CS) Total Link Pro activerse for menote management & firmwere updates Yes, included (Windows 10, Windows Server 2012 R2 & 2018, Windows Web Server, mac/CS) Total Link Pro activerse for menote management & firmwere updates Yes, included (Windows 10, Windows Server 2012 R2 & 2018, Windows Web Server, mac/CS) Total Link Pro activerse for menote management & firmwere updates Yes, included (Windows 10, Windows Server 2012 R2 & 2018, Windows Web Server, mac/CS) Max stor of pick pro area outsite of working surface Langth: 35 mm, Width: 473 mm Max stor of pick pro area outsite of working surface Langth: 15 mm, Width: 27 mm Depth of flocus on areal object (VE2 X3 mm) Gorm Lip	Converted widescreen output signals (16:9 and 16:10)	1080p FHD (1920 x 1080), 720p HD (1280 x 720)
White balance adjustment Automatic and manual Adjustable colur settings Yes Focus modes High speed continuous autobious, manual bous One-accent menu Yes, iscubicatione with swipe-through menus, basewort-protected advanced functions Sociation Link Pro-schwase for sende management & framwase updates Yes, iscubicatione with swipe-through menus, basewort-protected advanced functions Wax, object hight on working surface 10 - 270 mm (Tes / Ved) Xex, object pares Unimited Max, size of pick-up area Length: 355 mm, Width: 473 mm Max, size of pick-up area with optical zoon) Length: 55 mm, Width: 473 mm Min, see of pick-up area with optical zoon) Length: 10 mm, Width: 58 mm Min, see of pick-up area with optical zoon) Length: 10 mm, Width: 27 mm Min, see of pick-up area with optical zoon) Length: 10 mm, Width: 27 mm Depth of focus on small object (62 x 23 mm) 30 mm Depth of focus on small object (62 x 33 mm) 30 mm Depth of focus on small object (62 x 33 mm) 30 mm Depth of focus on small object (62 x 20 mm) 60 mm Length: 10 mm, Width: 27 mm 10 - 270 mm (Width: 27 mm) Depth of focus on small object (62 x 33 mm)	Image resolution	1300 lines
Adjustable colour settings Yes Focus modes High speed continuous autotoous, manual focus On-seem menu Yes, touchooreen with swice-housus autotoous, manual focus Volution Link Prosolware for remote management & firmware updates Yes, included Windows 10. Windows Stewer 2012 PZ & 2016, Windows Webb Server modOS) Free firmware updates Yes, via USB, LAN, and vSolution Link Pro Zoom / Lens type 24-2 Coom (12x optical, 2x digital) / Wide angle F-3.17 Max. doted height on working surface 110 - 270 mm (Rev / Wide) Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working surface Unlimited Max. size of pick-up area outside of working area Unlimited Depth of tocas on surfa optical, Zx dimm Offer Depth of tocas on surfa optical, Zx dimm Offer Depth of tocas o	Brightness control	Automatic and manual
Adjustable colour settings Yes Focus modes High seed continuous autofocus, manual focus Conscreen menu Yes, Lourbacerow Hith wayee through meru, Baseword protected advanced functions visiolinto Link No software for remote management & firmware updates Yes, via USB, LAN, and visiolinto Link Pro Zoom / Laws type 244-Zoom (12x, optical, 2x digital). Wile angle 16-3.17 Max, object height on working surface Length: 350 mm, Width: 473 mm Max, size of pick-up area Length: 350 mm, Width: 473 mm Max, size of pick-up area outside of working surface Unimited Min, size of pick-up area outside of working surface Length: 350 mm, Width: 473 mm Max, size of pick-up area outside of working surface Unimited Min, size of pick-up area outside of working surface Length: 35 mm Min, size of pick-up area outside of working surface Visit, Yes Dight of focus on allerage digkt 260 x270 mm Longth: 15 mm, Width: 27 mm Dight of focus on allerage digkt 260 x270 mm Toff mm Dight of focus on allerage object (260 x270 zm) Toff mm Vick Working, unacex, macKells, PIPI (Pickte Transfer Protocol) Yes Vick Working, unacex, maxells, PIPI (Pickte Transfer Protocol) Yes </td <td></td> <td>Automatic and manual</td>		Automatic and manual
On-screen menu Yes, touchscreen with swipe through menu & password-protected advanced kunctors visioution Link Pro software for remote management & firmware updates Yes, included Windows 10, Windows Sever 2012 R2 & 2016, Windows Web Server, macc06) Free Imware updates Yes, included Windows 10, Windows 2002 R2 & 2016, Windows Web Server, macc06) Wax, object height on working surface 110 - 270 rm (Tele / wide) Max, object height on working surface Unlimited Max, size of pick-up area outside of working surface Unlimited Min, size of pick-up area outside of working surface Unlimited Min, size of pick-up area outside of working surface Unlimited Min, size of pick-up area outside of working surface Unlimited Min, size of pick-up area (with digital zoom) Length: 15 mm, Width: 27 mm Depth of focus on small object (24 x 33 mm) 30 mm Depth of focus on surga object (380 x 270 mm) 100 mm Light source Acjustment-free, maintenance-free LED light system Refection free pickup area Yes, 192', for free ging to the tent or remote the unit UCC (Window, Linux, maccOS, IPTP Pickup Transfer Protocol Yes Volus, Hours, maccOS, PTP Pickup Transfer Protocol Yes UCC (Window, Linux, ma		Yes
vblution Link Pro software for remote management & firmware updates Yes, via USB, LAN, and vSolution Link Pro Zoom / Lens type 24x Zoom (12x optical, 2x digital / Wide argie f-3.17 Max. object height on working surface 110 - 270 mm (Tele / Wide) Max. size of pick-up area Length: 550 mm, Width: 73 mm Max. size of pick-up area Unlimited Min. size of pick-up area outside of working surface Unlimited Min. size of pick-up area outside of working surface Unlimited Min. size of pick-up area outside of working surface Unlimited Min. size of pick-up area outside of working surface Unlimited Min. size of pick-up area (with digital zoom) Length: 15 mm, Width: 27 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus on smal object (42 X 33 mm) 30 mm Depth of focus	Focus modes	High speed continuous autofocus, manual focus
vSolution Link Pro software for menote management & firmware updates Yes, included (Windows 10, Windows 20 are 2012 P2.8.2016, Windows Web Sarver, nac.OS) Pree firmware updates Yes, wa USS, LAN, and VSolution Link Pro Zoom / Lens type 24x Zoom (12x optical, 2x digital) (Wide angle fn-3.17 Max, object height on working surface Length: 355 mm, Width: 473 mm Max, size of pick-up area outside of working surface Unlimited Min, size of pick-up area (with optical zoom) Length: 35 mm, Width: 57 mm Min, size of pick-up area (with optical zoom) Length: 15 mm, Width: 27 mm Depth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large object (860 x 270 mm) 100 mm Lepth of focus on large	On-screen menu	
Zonn / Lens type 244 Zoon (12x optical, 2x digital) / Wide angle 1=3.17 Max. object height on working surface 110 - 270 mm (Tele / wide) Max. size of pick-up area Length: 355 mm, Width: 473 mm Max. size of pick-up area outside of working surface Unlimited Min. size of pick-up area outside of working surface Unlimited Min. size of pick-up area (with optical zoom) Length: 30 mm, Width: 27 mm Depth of focus on small object (42 x 33 mm) 30 mm Depth of focus on large object (80 x 270 mm) 100 mm Light source Adjustment-free, maintenance-free LED light system Reflecton-free pickup area Entre working area Vick Mindows, Linux, mexDS, PTP Picture Tensfer Protocol Yes Vick Mindows, Linux, mexDS, PTP Picture Tensfer Protocol Yes Patiating camera head Yes, 192°, for imaging to the fond or near the unit User programmable presets 3 Inage memory 63B Internal memory + unlimited storage on USB stick. External computer input / Input switch 1x HDM In Built- indigital scalar for the computer input Yes (processes the signal from HDM input) Inputs / Outputs 1x HDM In Length:	vSolution Link Pro software for remote management & firmware updates	
Max. object height on working surface 110 - 270 mm (fele / wide) Max. size of pick-up area Length: 355 mm, Width: 473 mm Max. size of pick-up area (with optical zoom) Length: 30 mm, Width: 53 mm Min. size of pick-up area (with optical zoom) Length: 15 mm, Width: 27 mm Depth of focus on small object (42 x 33 mm) 30 mm Depth of focus on small object (42 x 33 mm) 30 mm Depth of focus on large object (360 x 270 mm) 100 mm Light source Adjustment-free, maintenance-free LED light system Reflection-free pickup area Entire working area UVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol) Yes Potating camera head Yes, 192°, for imaging to the front or rear the unit User programmable presets 3 Image memory 6BB internal memory + unlimited storage on USB stick Latimal digital scaler for the computer input Yes (processes the signal from HOMI input) Inputs / Outputs Ya HOMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN port LAN web interface Yes (Vis LAN and USB) Dimensions in operation (Lx W x H) 225 x 175 x 410 mm Weight 1.70 kg Anti-therd kerkes Fuck (Kensington® Lock) and table lock bolt Power External devices power pack 12% multi range 100-2400/18W (length of power cord 1.5m) Indu	Free firmware updates	Yes, via USB, LAN, and vSolution Link Pro
Max. size of pick-up area Length: 355 mm, Width: 473 mm Max. size of pick-up area outside of working surface Unlimited Min. size of pick-up area (with optical zoom) Length: 30 mm, Width: 50 mm Min. size of pick-up area (with optical zoom) Length: 15 mm, Width: 27 mm Depth of focus on small object (42 x 30 mm) 30 mm Depth of focus on small object (42 x 30 mm) 30 mm Depth of focus on small object (42 x 30 mm) 100 mm Light source Adjustment-free, maintenance-free LED light system Reflection-free pickup area Entire working area UVC (Mindows, Linux, macOS), PTP Picture Transfer Protocol Yes Rotating camera head Yes, 192°, for imaging to the front or rear the unit User programmable presets 3 Image memory GGB internal memory - unlimited storage on USB stick External computer input / hput switch 1x HDM In Euli-in digital scaler for the computer input Yes (processes the signal from HDMI input) Inputs / Outputs 1x HDM In, tx USB 3.0 device port, 1x USB 2.0 host port, 1x LAN port LAN web interface Yes (processes the Signal from HDMI input) Inputs / Outputs 1x HDM In, tx USB 3.0 device port, 1x USB 2.0 host port, 1x LAN port LAN web interface Yes (vicesses to CSD menu, but no live image and controls) Roear control APIs available for contorlin	Zoom / Lens type	24x Zoom (12x optical, 2x digital) / Wide angle f=3.17
Max. size of pick-up area outside of working surfaceUnimitedMin. size of pick-up area (with optical zoom)Length: 30 mm, Width: 53 mmMin. size of pick-up area (with digital zoom)Length: 15 mm, Width: 27 mmDepth of focus on small object (42 x 33 mm)90 mmDepth of focus on sinal object (46 x 270 mm)100 mmLight sourceAdjustment-free, maintenance-free LED light systemReflection-free pickup areaEntre working areaUVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesPotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8GB Internal memory + unimited storage on USB stickExternal computer input / Input switch1x HDM InBuilt-in digital scalar for the computer inputYes (proceases the signal from HDM input)Inputs / Outputs1x HDM Out, 1x HDM Ion, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to SDD menu, but no live image and controls)Room on trol APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boitPowerExternal desktop power pack 12V: mult range 100-2400,18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesPower supply	Max. object height on working surface	110 - 270 mm (Tele / wide)
Mn. size of pick-up area (with optical zoom)Length: 30 mm, Width: 53 mmMn. size of pick-up area (with digital zoom)Length: 15 mm, Width: 27 mmDepth of focus on small object (42 x 33 mm)30 mmDepth of focus on small object (360 x 270 mm)100 mmLight sourceAdjustment-free, maintenance-free LED light systemReflection-free pickup areaEntire working areaUVC (Mndows, Linux, macOS), PTP (Picture Transfer Protocol)YesVotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuil-In digital scaler for the computer inputYes (srocesses the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 110 mmWeight1.70 kgAnti-thet devicesT-Lock (Kensington® Lock) and table lock botPowerExternal desktop power pack 12V: multi range 100-24OV.18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesDay-erase working surface	Max. size of pick-up area	Length: 355 mm, Width: 473 mm
Nin. size of pick-up area (with optical zoom)Langth: 30 mm, Width: 37 mmDepth of focus on small object (42 x 33 mm)30 mmDepth of focus on small object (42 x 33 mm)100 mmLight sourceAdjustment-Hee, maintenance-free LED light systemLight sourceAdjustment-Hee, maintenance-free LED light systemReflection-free pickup areaThree working areaUVC Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory6GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI inBuil-in digital scaler for the computer inputYes (rocesses the signal from HDMI input)Inputs / Outputs1x HDMI in, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (via LAN and USS)Brown for Age and uSS)Yes (via LAN and USS)Dimensions in operation (Lx W x H)1.70 kgAnti-thet devicesFlock (Kensington@ Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesDay-erase working surface	Max. size of pick-up area outside of working surface	Unlimited
Nin. size of pick-up area (with digital zoom)Length: 15 mm, Width: 27 mmDepth of focus on small object (42 x 33 mm)30 mmDepth of focus on large object (360 x 270 mm)100 mmLight sourceAdjustment-free, maintenance-free LED light systemReflection-free pickup areaEntire working areaUVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory80B internal memory + unlimited storage on USB stickExternal computer input / Input switchtx HDMI InInputs / Outputstx HDMI Un, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to CSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmVeight1.70 kgAnti-theft devicesT-Look (Kensington@ Lock) and table lock boltPowerExternal cesstop servicesPower upplyOptional accessoriesOptional accessoriesDower supply	Min. size of pick-up area (with optical zoom)	
Depth of focus on large object (360 x 270 nm)100 nmLight sourceAdjustment-free, maintenance-free LED light systemReflection-free pickup areaEntire working areaUVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memoryBGB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI inBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to CSD menu, but no live image and controls)Room control APIs available for controllingYes (xia LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V.18W (length of power cord 1.5m)Included accessoriesDy-erase working surface		
Light sourceAdjustment-free, maintenance-free LED light systemReflection-free pickup areaEntire working areaUVC (Windows, Linux, mac/OS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 122: multi range 100-2400,18W (length of power cord 1.5m)Included accessoriesDry-erase working surface	Depth of focus on small object (42 x 33 mm)	30 mm
Reflection-free pickup areaEntire working areaUVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8CB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Un, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Poem control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington@ Lock) and table lock botlPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesDy-erase working surface	Depth of focus on large object (360 x 270 mm)	100 mm
UVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)YesRotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (via LAN and USB)Pome control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmVeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V, 18W (length of power cord 1.5m)Included accessoriesDry-erase working surface	Light source	Adjustment-free, maintenance-free LED light system
Rotating camera headYes, 192°, for imaging to the front or rear the unitUser programmable presets3Image memory8GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmVeight1.70 kgAnti-theff devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesDry-erase working surface	Reflection-free pickup area	Entire working area
User programmable presets3Image memorySGB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmVeight1.70 kgAnti-theft devicesF-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V, 18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesDry-erase working surface	UVC (Windows, Linux, macOS), PTP (Picture Transfer Protocol)	Yes
Image memory8GB internal memory + unlimited storage on USB stickExternal computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington@ Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V, 18W (length of power cord 1.5m)Included accessoriesDy-erase working surface	Rotating camera head	Yes, 192°, for imaging to the front or rear the unit
External computer input / Input switch1x HDMI InBuilt-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesDry-erase working surface	User programmable presets	3
Built-in digital scaler for the computer inputYes (processes the signal from HDMI input)Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesDry-erase working surface	Image memory	8GB internal memory + unlimited storage on USB stick
Inputs / Outputs1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN portLAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesPower supplyOptional accessoriesDry-erase working surface	External computer input / Input switch	1x HDMI In
LAN web interfaceYes (access to OSD menu, but no live image and controls)Room control APIs available for controllingYes (via LAN and USB)Dimensions in operation (L x W x H)225 x 175 x 410 mmWeight1.70 kgAnti-theft devicesT-Lock (Kensington® Lock) and table lock boltPowerExternal desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)Included accessoriesDy-erase working surface	Built-in digital scaler for the computer input	Yes (processes the signal from HDMI input)
LAN web interface Yes (access to OSD menu, but no live image and controls) Room control APIs available for controlling Yes (via LAN and USB) Dimensions in operation (L x W x H) 225 x 175 x 410 mm Weight 1.70 kg Anti-theft devices T-Lock (Kensington® Lock) and table lock bolt Power External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m) Included accessories Power supply Optional accessories Dry-erase working surface		1x HDMI Out, 1x HDMI In, 1x USB 3.0 device port, 1x USB 2.0 host port, 1x LAN port
Dimensions in operation (L x W x H) 225 x 175 x 410 mm Weight 1.70 kg Anti-theft devices T-Lock (Kensington® Lock) and table lock bolt Power External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m) Included accessories Power supply Optional accessories Dry-erase working surface		Yes (access to OSD menu, but no live image and controls)
Weight 1.70 kg Anti-theft devices T-Lock (Kensington® Lock) and table lock bolt Power External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m) Included accessories Power supply Optional accessories Dry-erase working surface	Room control APIs available for controlling	Yes (via LAN and USB)
Anti-theft devices T-Lock (Kensington® Lock) and table lock bolt Power External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m) Included accessories Power supply Optional accessories Dry-erase working surface	Dimensions in operation (L x W x H)	225 x 175 x 410 mm
Power External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m) Included accessories Power supply Optional accessories Dry-erase working surface	Weight	1.70 kg
Included accessories Power supply Optional accessories Dry-erase working surface	Anti-theft devices	T-Lock (Kensington® Lock) and table lock bolt
Optional accessories Dry-erase working surface	Power	External desktop power pack 12V: multi range 100-240V,18W (length of power cord 1.5m)
Optional accessories Dry-erase working surface		Power supply
Warranty / Made in 5 years / EU Austria		Dry-erase working surface
	Warranty / Made in	5 years / EU Austria

Your WolfVision Partner:

Head Office:

WolfVision GmbH 6833 Klaus / Austria Tel. +43 5523 52250 wolfvision@wolfvision.com

UK Sales Office WolfVision UK Ltd. Tel. +44 1628 968660 uk@wolfvision.com Japan Sales Office WolfVision Co. Ltd. Tel. +81 3 6233 9465 japan@wolfvision.com

Middle East Sales Office WolfVision Middle East (Dubai) Tel. +971 5617 40008 middle-east@wolfvision.com



USA Sales Office WolfVision, Inc. Tel. +1 770 931 6802 usa@wolfvision.com

Asia Sales Office WolfVision Pte. Ltd. (Singapore) Tel. +65 6636 1268 asia@wolfvision.com



Switzerland Sales Office WolfVision Switzerland Tel. +41 71 571 38 00 switzerland@wolfvision.com

Germany Sales Office WolfVision GmbH Tel. +43 5523 52250 germany@wolfvision.com Nordic Sales Office WolfVision Nordic (Norway) Tel. +47 9186 9736 nordic@wolfvision.com

Available in selected markets only 1 Design and specifications subject to change! | Printed in Germany, January 2024

India Sales Office WolfVision India Tel. +91 9136009722 india@wolfvision.com